



Magnum® Plus Flex roundsling

WLL ¹ [kg]	approx. thick under load A [mm]	approx. wide under load B [mm]	L1 min. [m]	L2 max. [m]	approx. weight running m [kg]	Color coding	Shackle combination	
							Shackle Green Pin®	[t]
10.000	18	88	2	60	2.1	orange		12
20.000	22	143	2	60	4.3	orange		25
30.000	25	180	3	60	6.5	orange		35
40.000	30	224	3	60	7.5	orange		42.5
50.000	35	320	3	60	10.2	orange		55

Order numbers [Global Item Number, SSDI/SSD] by length/nominal load capacity:

WLL ¹	3m	4m	5m	6m	7m	8m
10.000	2027060	2027061	2027062	2027063	2027064	2027065
20.000	2027072	2027073	2027074	2027075	2027076	2027077
30.000	2027677	2027678	2027679	2027680	2027681	2027682
40.000	2027078	2027079	2027080	2027081	2027082	2027083
50.000	2027084	2027085	2027086	2027087	2027088	2027089

- Operating temperature °C: - 30 bis + 100°C
- Safety factor: 1:7
- Inner material: Polyester (PES)
- Hose material: Polyester (PES), Elasthan (EL)
- Labeling: Unique label including RFID transponder
- Norm: Based on DIN EN 1492-2
- Testing: Type examination
- Customs tariff number: 63079098

Operating instructions and declaration of conformity are included with every Magnum® Plus Flex roundsling and can be downloaded from www.spanset.com.

1 WLL - working load limit

