


Grillete 6P
Lira con pasador y tuerca



Descripción Grillete 6P, lira con pasador y tuerca.

Conforme a • Norma EN13889.

Tolerancias

- Diámetro C:
 - de 0,5t a 2t inclusive: +1,5/- 1 mm
 - de 3,25t a 12t inclusive: +/- 2,5 mm
 - de 13,5t a 25t inclusive: +/- 3 mm
- Diámetro del pasador B:
 - de 0,5t a 2t inclusive: +/- 1 mm
 - de 3,25t a 25t inclusive: +/- 2 mm
- Anchura interior en el pasador E:
 - de 0,5t a 2t inclusive: +/- 2,5 mm
 - de 3,25t a 9,5t inclusive: +/- 3 mm
 - de 12t a 25t inclusive: +/- 4 mm

Ovalización admisible del diámetro C + 10% para los tamaños de 3,25t hasta 17t inclusive, + 25% para el tamaño de 25t (iguales tolerancias que arriba).

Referencia	CMU [Ton.]	A [mm]	B [mm]	Ø C [mm]	D [mm]	E [mm]
G4-6-005	0.5	28.5	8	6	10	13
G4-6-007	0.75	31	10	8	10.5	14
G4-6-010	1	37	11	10	13	17
G4-6-015	1.5	43	13	11	14.5	18
G4-6-020	2	48	16	13	16.5	21
G4-6-032	3.25	60	19	16	21.5	27
G4-6-047	4.75	71	22	19	25.5	32
G4-6-065	6.5	84	25	22	29	37
G4-6-085	8.5	95	28	25	34	43
G4-6-095	9.5	108	32	30	37	46
G4-6-120	12	119	35	32	41	51
G4-6-135	13.5	132	38	35	45	57
G4-6-170	17	146	41	38	49	60
G4-6-250	25	178	50	45	63.5	73
G4-6-350	35	197	57	50	73	83
G4-6-550	55	260	70	65	90	105

SpanSet S.A

Tel. 943 692 600

Fax. 943 692 575

Email sse@spanset.es

www.spanset.es

