



**Descripción** Cáncamo giratorio.

**Características**

- Giro de 360°
- Ajustable en la dirección de la fuerza, con cojinete de deslizamiento.

**Conforme a**

- Norma EN 1677-4.

Referencia	Rosca [M]	CMU [t]	Peso [kg]	A [mm]	B [mm]	C [mm]	D [Ø mm]	E [Ø mm]	F [mm]	K [Ø mm]	L [mm]	Ch [mm]
XOPSR-08	M08	0.3	0.12	35	11	9	25	25.5	30	46	12	6
XOPSR-10	M10	0.4	0.12	33.7	10	9.8	25	25.5	30	46	15	6
XOPSR-12	M12	0.75	0.2	41.5	12.5	11.5	30	30.6	36.5	55.5	18	8
XOPSR-14	M14	0.75	0.2	41.5	12.5	11.5	30	30.6	36.5	55.5	18	8
XOPSR-16	M16	1.5	0.35	49.5	14.5	15.7	35	36.5	42	64.5	24	10
XOPSR-18	M18	1.5	0.35	49.5	14.5	15.7	35	36.5	42	64.5	24	10
XOPSR-20	M20	2.3	0.6	58	16	18	40	42	52.5	74.5	30	12
XOPSR-22	M22	2.3	0.6	58	16	18	40	42	52.5	74.5	30	12
XOPSR-24	M24	3.2	1	69	20.5	22	49	50	61	90	36	12
XOPSR-27	M27	3.2	1	69	20.5	22	49	50	61	90	36	12
XOPSR-30	M30	4.5	2	86	25.5	28	60	66	75	111	45	17
XOPSR-33	M33	4.5	2	86	25.5	28	60	66	75	111	45	17
XOPSR-36	M36	7	3.4	105	32	30	74	77	96.5	135	55	22
XOPSR-42	M42	9	5.7	118	38	37	82	87	110	158	65	24
XOPSR-48	M48	12	8.5	137	43	38	95	102	124.5	180	72	27

EN1677-4

**SpanSet S.A**

Tel. 943 692 600

Fax. 943 692 575

Email sse@spanset.es

www.spanset.es