



Descrição Olhal giratório.

- Características**
- Rotação 360°.
 - Ajustável na direção da força, com chumaceira de deslizamento.

Norma • EN1677-4

Referência	Rosca [d]	CMU [t]	Peso [kg]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	K [mm]	L [mm]
XOPSR-08	M8	0.3	0.12	33.7	10	9.8	25	25.5	46	12
XOPSR-10	M10	0.4	0.12	33.7	10	9.8	25	25.5	46	15
XOPSR-12	M12	0.75	0.2	41.5	12.5	11.5	30	30.6	55.5	18
XOPSR-14	M14	0.75	0.2	41.5	12.5	11.5	30	30.6	55.5	18
XOPSR-16	M16	1.5	0.35	49.5	14.5	15.7	35	36.5	64.5	24
XOPSR-18	M18	1.5	0.35	49.5	14.5	15.7	35	36.5	64.5	24
XOPSR-20	M20	2.3	0.6	58	16	18	40	42	74.5	30
XOPSR-22	M22	2.3	0.6	58	16	18	40	42	74.5	30
XOPSR-24	M24	3.2	1	69	20.5	22	49	50	90	36
XOPSR-27	M27	3.2	1	69	20.5	22	49	50	90	36
XOPSR-30	M30	4.5	2	86	25.5	28	60	66	111	45
XOPSR-33	M33	4.5	2	86	25.5	28	60	66	111	45
XOPSR-36	M36	7	3.4	105	32	30	74	77	135	55
XOPSR-42	M42	9	5.7	118	38	37	82	87	158	65
XOPSR-48	M48	12	8.5	137	43	38	95	102	180	72

SpanSet S.A

Tel. +34 943 692 600

Fax. +34 943 692 575

Email sse@spanset.es

www.spanset.pt

