



Description Anneau de levage inclinable, à souder.

Caractéristiques

- Fabriqué en acier grande résistance.
- Peinture époxy.

Conforme à

- Norme 1677-4.

Référence	Joint de soudure	Capacité de charge [t]		Poids [kg]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H Stand.
		$\frac{\delta}{6}$	$\frac{6}{\delta}$									
XOW1,5	HV 5 + 3 a	1,5	1,5	0,39	14	65	38	25	66	16	31	79
XOW2,5	HV 7 + 3 a	2,5	2,5	0,59	16	75	45	27	77	18	34,5	91
XOW4	HV 8 + 3 a	4	4	0,87	18	84	51	32	87	20	40	102
XOW6,7	HV 12 + 4 a	6,7	6,7	2,23	24	117	67,3	44	115	26	58,5	141
XOW10	HV 16 + 4 a	10	10	3,33	31	126	67	55	129	28,5	70,5	157
XOW16	HV 25 + 6 a	16	16	9,28	45	174	100	69	190	42	87	219

SpanSet SARL

Tél. 04 72 47 69 90

Fax. 04 72 47 00 19

Email commercial@spanset.fr

www.spanset.fr

