



MagnumPlus Strong hold for heavy loads

Label	Contact Thickness Under Load [mm]	Dimension L1 max [m]	Dimension L1 min [m]	Dimension L1 [m]	WLL [kg]	WLL [t]	Weight Net [kg]	Weight per Meter [kg/m]
MagnumPlus 10000 2m	12	30	1	2	10000	10	4.4	2.2
MagnumPlus 10000 2.5m	12	30	1	2.5	10000	10	5.5	2.2
MagnumPlus 10000 3m	12	30	1	3	10000	10	6.6	2.2
MagnumPlus 10000 4m	12	30	1	4	10000	10	9.3	2.2
MagnumPlus 10000 5m	12	30	1	5	10000	10	11.5	2.2
MagnumPlus 10000 6m	12	30	1	6	10000	10	13.7	2.2
MagnumPlus 10000 7m	12	30	1	7	10000	10	15.9	2.2
MagnumPlus 10000 8m	12	30	1	8	10000	10	18.1	2.2
MagnumPlus 15000 2m	16	30	1	2	15000	15	5.4	2.7
MagnumPlus 15000 2.5m	16	30	1	2.5	15000	15	6.75	2.7
MagnumPlus 15000 3m	16	30	1	3	15000	15	8.1	2.7
MagnumPlus 15000 4m	16	30	1	4	15000	15	13.3	2.7
MagnumPlus 15000 5m	16	30	1	5	15000	15	16.5	2.7
MagnumPlus 15000 6m	16	30	1	6	15000	15	19.7	2.7
MagnumPlus 15000 7m	16	30	1	7	15000	15	22.9	2.7
MagnumPlus 15000 8m	16	30	1	8	15000	15	26.1	2.7
MagnumPlus 20000 2m	18	30	1.3	2	20000	20	8	4
MagnumPlus 20000 2.5m	18	30	1.3	2.5	20000	20	10	4
MagnumPlus 20000 3m	18	30	1.3	3	20000	20	12	4
MagnumPlus 20000 4m	18	30	1.3	4	20000	20	18.1	4



MagnumPlus

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Label	Contact Thickness Under Load [mm]	Dimension L1 max [m]	Dimension L1 min [m]	Dimension L1 [m]	WLL [kg]	WLL [t]	Weight Net [kg]	Weight per Meter [kg/m]
MagnumPlus 20000 5m	18	30	1.3	5	20000	20	22.5	4
MagnumPlus 20000 6m	18	30	1.3	6	20000	20	26.9	4
MagnumPlus 20000 7m	18	30	1.3	7	20000	20	31.3	4
MagnumPlus 20000 8m	18	30	1.3	8	20000	20	35.7	4
MagnumPlus 25000 2.5m	25	30	1.3	2.5	25000	25	12.5	5
MagnumPlus 25000 3m	25	30	1.3	3	25000	25	15	5
MagnumPlus 25000 4m	25	30	1.3	4	25000	25	22.9	5
MagnumPlus 25000 5m	25	30	1.3	5	25000	25	28.5	5
MagnumPlus 25000 6m	25	30	1.3	6	25000	25	34.1	5
MagnumPlus 25000 7m	25	30	1.3	7	25000	25	39.7	5
MagnumPlus 25000 8m	25	30	1.3	8	25000	25	45.3	5
MagnumPlus 30000 2.5m	19	30	1.3	2.5	30000	30	16.25	6.5
MagnumPlus 30000 3m	19	30	1.3	3	30000	30	19.5	6.5
MagnumPlus 30000 4m	19	30	1.3	4	30000	30	30.1	6.5
MagnumPlus 30000 5m	19	30	1.3	5	30000	30	37.5	6.5
MagnumPlus 30000 6m	19	30	1.3	6	30000	30	44.9	6.5
MagnumPlus 30000 7m	19	30	1.3	7	30000	30	52.3	6.5
MagnumPlus 30000 8m	19	30	1.3	8	30000	30	59.7	6.5
MagnumPlus 40000 3m	22	30	3	3	40000	40	29.1	9.7
MagnumPlus 40000 4m	22	30	3	4	40000	40	40.5	9.7
MagnumPlus 40000 5m	22	30	3	5	40000	40	50.5	9.7



MagnumPlus

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Label	Contact Thickness Under Load [mm]	Dimension L1 max [m]	Dimension L1 min [m]	Dimension L1 [m]	WLL [kg]	WLL [t]	Weight Net [kg]	Weight per Meter [kg/m]
MagnumPlus 40000 6m	22	30	3	6	40000	40	60.5	9.7
MagnumPlus 40000 7m	22	30	3	7	40000	40	70.5	9.7
MagnumPlus 40000 8m	22	30	3	8	40000	40	80.5	9.7
MagnumPlus 40000 15m	22	30	3	15	40000	40	-	9.7
MagnumPlus 50000 4m	24	30	3	4	50000	50	52.5	12.5
MagnumPlus 50000 5m	24	30	3	5	50000	50	65.5	12.5
MagnumPlus 50000 6m	24	30	3	6	50000	50	78.5	12.5
MagnumPlus 50000 7m	24	30	3	7	50000	50	91.5	12.5
MagnumPlus 50000 8m	24	30	3	8	50000	50	104.5	12.5
MagnumPlus 60000 4m	27	30	3	4	60000	60	59.7	16.6
MagnumPlus 60000 5m	27	30	3	5	60000	60	74.5	16.6
MagnumPlus 60000 6m	27	30	3	6	60000	60	89.3	16.6
MagnumPlus 60000 7m	27	30	3	7	60000	60	104.1	16.6
MagnumPlus 60000 8m	27	30	3	8	60000	60	118.9	16.6
MagnumPlus 80000 4m	47	30	3	4	80000	80	80.5	20.8
MagnumPlus 80000 5m	47	30	3	5	80000	80	100.5	20.8
MagnumPlus 80000 6m	47	30	3	6	80000	80	120.5	20.8
MagnumPlus 80000 7m	47	30	3	7	80000	80	140.5	20.8
MagnumPlus 80000 8m	47	30	3	8	80000	80	160.5	20.8
MagnumPlus 100000 4m	49	30	3	4	100000	100	104.5	24.3
MagnumPlus 100000 5m	49	30	3	5	100000	100	130.5	24.3



MagnumPlus

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Label	Contact Thickness Under Load [mm]	Dimension L1 max [m]	Dimension L1 min [m]	Dimension L1 [m]	WLL [kg]	WLL [t]	Weight Net [kg]	Weight per Meter [kg/m]
MagnumPlus 100000 6m	49	30	3	6	100000	100	156.5	24.3
MagnumPlus 100000 7m	49	30	3	7	100000	100	182.5	24.3
MagnumPlus 100000 8m	49	30	3	8	100000	100	208.5	24.3
MagnumPlus 125000 10m	-	-	-	10	125000	125	-	-
MagnumPlus 125000 15m	-	-	-	15	125000	125	-	-

ORDER NUMBERS

Dimension L1	10000 kg	15000 kg	20000 kg	25000 kg	30000 kg	40000 kg	50000 kg	60000 kg	80000 kg	100000 kg	125000 kg
2	2020851	2027560	2023220	-	-	-	-	-	-	-	-
2.5	2020997	2020999	2021001	2021003	2021005	-	-	-	-	-	-
3	2020998	2021000	2021002	2021004	2021006	2021008	-	-	-	-	-
4	2002743	2002745	2002747	2002749	2002751	2002753	2002755	2002757	2002759	2002761	-
5	2002744	2002746	2002748	2002750	2002752	2002754	2002756	2002758	2002760	2002762	-
6	2003231	2003233	2003235	2003237	2003239	2003241	2003243	2003245	2003247	2003249	-
7	2003232	2003234	2003236	2003238	2003240	2003242	2003244	2003246	2003248	2003250	-
8	2003728	2003729	2003730	2003731	2003732	2003733	2003734	2003735	2003736	2003737	-
10	-	-	-	-	-	-	-	-	-	-	2017504
15	-	-	-	-	-	2020974	-	-	-	-	2024149

■ Norms	EN 1492-2: 2000
■ Main Material	Polyester
■ Temperature Range	- 40 bis + 100°C
■ Label Protection	Yes
■ Safety Factor	7:1
■ Packaging Unit (PU)	pcs
■ Packaging Unit (PU) Content	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - Nutzlänge.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.



MagnumPlus

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom