



PowerFlex - Abrasion resistance coating flat sling

High abrasion resistance lifting sling with Powerflex coating on both side

Label	Colour	Dimension L1 min [m]	Dimension L1 [m]	WLL [kg]	WLL [t]	Webbing Width B [mm]	Weight Net [kg]
PB 1000-P2 2m	Purple	1	2	1000	1	30	0.7
PB 1000-P2 3m	Purple	1	3	1000	1	30	1
PB 1000-P2 4m	Purple	1	4	1000	1	30	1.3
PB 1000-P2 5m	Purple	1	5	1000	1	30	1.6
PB 1000-P2 6m	Purple	1	6	1000	1	30	1.9
PB 2000-P2 1.25m	Green	1	1.25	2000	2	60	1.2
PB 2000-P2 2m	Green	1	2	2000	2	60	1.6
PB 2000-P2 2.5m	Green	1	2.5	2000	2	60	1.9
PB 2000-P2 3m	Green	1	3	2000	2	60	2.2
PB 2000-P2 4m	Green	1	4	2000	2	60	2.8
PB 2000-P2 5m	Green	1	5	2000	2	60	3.4
PB 2000-P2 6m	Green	1	6	2000	2	60	4
PB 2000-P2 7m	Green	1	7	2000	2	60	4.5
PB 3000-P2 2m	Yellow	1.3	2	3000	3	90	2.1
PB 3000-P2 3m	Yellow	1.3	3	3000	3	90	2.9
PB 3000-P2 4m	Yellow	1.3	4	3000	3	90	3.7
PB 3000-P2 5m	Yellow	1.3	5	3000	3	90	4.5
PB 3000-P2 6m	Yellow	1.3	6	3000	3	90	5.3
PB 4000-P2 2m	Grey	1.3	2	4000	4	120	2.9
PB 4000-P2 3m	Grey	1.3	3	4000	4	120	4



PowerFlex - Abrasion resistance coating flat sling

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Label	Colour	Dimension L1 min [m]	Dimension L1 [m]	WLL [kg]	WLL [t]	Webbing Width B [mm]	Weight Net [kg]
PB 4000-P2 4m	Grey	1.3	4	4000	4	120	5.1
PB 4000-P2 5m	Grey	1.3	5	4000	4	120	6.2
PB 4000-P2 6m	Grey	1.3	6	4000	4	120	7.3
PB 5000-P2 2m	Red	1.5	2	5000	5	150	3.8
PB 5000-P2 3m	Red	1.5	3	5000	5	150	5.2
PB 5000-P2 4m	Red	1.5	4	5000	5	150	6.6
PB 5000-P2 5m	Red	1.5	5	5000	5	150	8
PB 5000-P2 6m	Red	1.5	6	5000	5	150	9.4

ORDER NUMBERS

End Fitting Component	WLL	1.25 m	2 m	2.5 m	3 m	4 m	5 m	6 m	7 m
-	1000	-	2015456	-	2015457	2015458	2015459	2015460	-
-	2000	2015461	2015462	2015463	2015464	2015465	2015466	2015467	2015468
-	3000	-	2015469	-	2015470	2015471	2015472	2015473	-
-	4000	-	2015474	-	2015475	2015476	2015477	2015478	-
-	5000	-	2015479	-	2015480	2015481	2015482	2015483	-

■ Norms	EN 1492-1: 2000
■ End Fitting Component	-
■ Belt Layers	2
■ Main Material	Polyester
■ Temperature Range	-40°C bis +100°C
■ Label Protection	Yes
■ Safety Factor	7:1
■ Packaging Unit (PU) Content	1
■ Packaging Unit (PU)	pcs



PowerFlex - Abrasion resistance coating flat sling

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom