



PowerFlex

High abrasion resistance lifting sling with Powerflex coating on both side

| Label | Colour | Dimension L1 min [m] | Dimension L1 [m] | WLL kg [kg] | Webbing Width B [mm] | Weight Net [kg] |
|------------------|--------|----------------------|------------------|-------------|----------------------|-----------------|
| PB 1000-P2 2m | Purple | 1 | 2 | 1000 | 30 | 0.7 |
| PB 1000-P2 3m | Purple | 1 | 3 | 1000 | 30 | 1 |
| PB 1000-P2 4m | Purple | 1 | 4 | 1000 | 30 | 1.3 |
| PB 1000-P2 5m | Purple | 1 | 5 | 1000 | 30 | 1.6 |
| PB 1000-P2 6m | Purple | 1 | 6 | 1000 | 30 | 1.9 |
| PB 2000-P2 1.25m | Green | 1 | 1.25 | 2000 | 60 | 1.2 |
| PB 2000-P2 2m | Green | 1 | 2 | 2000 | 60 | 1.6 |
| PB 2000-P2 2.5m | Green | 1 | 2.5 | 2000 | 60 | 1.9 |
| PB 2000-P2 3m | Green | 1 | 3 | 2000 | 60 | 2.2 |
| PB 2000-P2 4m | Green | 1 | 4 | 2000 | 60 | 2.8 |
| PB 2000-P2 5m | Green | 1 | 5 | 2000 | 60 | 3.4 |
| PB 2000-P2 6m | Green | 1 | 6 | 2000 | 60 | 4 |
| PB 2000-P2 7m | Green | 1 | 7 | 2000 | 60 | 4.5 |
| PB 3000-P2 2m | Yellow | 1.3 | 2 | 3000 | 90 | 2.1 |
| PB 3000-P2 3m | Yellow | 1.3 | 3 | 3000 | 90 | 2.9 |
| PB 3000-P2 4m | Yellow | 1.3 | 4 | 3000 | 90 | 3.7 |
| PB 3000-P2 5m | Yellow | 1.3 | 5 | 3000 | 90 | 4.5 |
| PB 3000-P2 6m | Yellow | 1.3 | 6 | 3000 | 90 | 5.3 |
| PB 4000-P2 2m | Grey | 1.3 | 2 | 4000 | 120 | 2.9 |
| PB 4000-P2 3m | Grey | 1.3 | 3 | 4000 | 120 | 4 |
| PB 4000-P2 4m | Grey | 1.3 | 4 | 4000 | 120 | 5.1 |
| PB 4000-P2 5m | Grey | 1.3 | 5 | 4000 | 120 | 6.2 |
| PB 4000-P2 6m | Grey | 1.3 | 6 | 4000 | 120 | 7.3 |
| PB 5000-P2 2m | Red | 1.5 | 2 | 5000 | 150 | 3.8 |
| PB 5000-P2 3m | Red | 1.5 | 3 | 5000 | 150 | 5.2 |
| PB 5000-P2 4m | Red | 1.5 | 4 | 5000 | 150 | 6.6 |



PowerFlex

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

| Label | Colour | Dimension L1 min [m] | Dimension L1 [m] | WLL kg [kg] | Webbing Width B [mm] | Weight Net [kg] |
|---------------|--------|----------------------|------------------|-------------|----------------------|-----------------|
| PB 5000-P2 5m | Red | 1.5 | 5 | 5000 | 150 | 8 |
| PB 5000-P2 6m | Red | 1.5 | 6 | 5000 | 150 | 9.4 |

ORDER NUMBERS

| End Fitting Component | WLL kg | 1.25 m | 2 m | 2.5 m | 3 m | 4 m | 5 m | 6 m | 7 m |
|-----------------------|--------|---------|---------|---------|---------|---------|---------|---------|---------|
| - | 1000 | - | 2015456 | - | 2015457 | 2015458 | 2015459 | 2015460 | - |
| - | 2000 | 2015461 | 2015462 | 2015463 | 2015464 | 2015465 | 2015466 | 2015467 | 2015468 |
| - | 3000 | - | 2015469 | - | 2015470 | 2015471 | 2015472 | 2015473 | - |
| - | 4000 | - | 2015474 | - | 2015475 | 2015476 | 2015477 | 2015478 | - |
| - | 5000 | - | 2015479 | - | 2015480 | 2015481 | 2015482 | 2015483 | - |

| | |
|-------------------------------|------------------|
| ■ Norms | EN 1492-1: 2000 |
| ■ End Fitting Component | - |
| ■ Belt Layers | 2 |
| ■ Main Material | Polyester |
| ■ Temperature Range | -40°C bis +100°C |
| ■ Safety Factor | 7:1 |
| ■ Label Protection | Yes |
| ■ Packaging Unit (PU) | pcs |
| ■ Packaging Unit (PU) Content | 1 |



PowerFlex

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom