



## PowerFlex with D-Rings

High abrasion resistance lifting sling with Powerflex coating on both side

| Label            | Dimension L1 min [m] | Dimension L1 [m] | WLL kg [kg] | Webbing Width B [mm] |
|------------------|----------------------|------------------|-------------|----------------------|
| PB 1000-P2-DD 2m | 1                    | 2                | 1000        | 30                   |
| PB 1000-P2-DD 3m | 1                    | 3                | 1000        | 30                   |
| PB 1000-P2-DD 4m | 1                    | 4                | 1000        | 30                   |
| PB 1000-P2-DD 5m | 1                    | 5                | 1000        | 30                   |
| PB 1000-P2-DD 6m | 1                    | 6                | 1000        | 30                   |
| PB 1000-P2-DD 8m | 1                    | 8                | 1000        | 30                   |
| PB 2000-P2-DD 2m | 1                    | 2                | 2000        | 60                   |
| PB 2000-P2-DD 3m | 1                    | 3                | 2000        | 60                   |
| PB 2000-P2-DD 4m | 1                    | 4                | 2000        | 60                   |
| PB 2000-P2-DD 5m | 1                    | 5                | 2000        | 60                   |
| PB 2000-P2-DD 6m | 1                    | 6                | 2000        | 60                   |
| PB 2000-P2-DD 8m | 1                    | 8                | 2000        | 60                   |
| PB 3000-P2-DD 2m | 1                    | 2                | 3000        | 90                   |
| PB 3000-P2-DD 3m | 1                    | 3                | 3000        | 90                   |
| PB 3000-P2-DD 4m | 1                    | 4                | 3000        | 90                   |
| PB 3000-P2-DD 5m | 1                    | 5                | 3000        | 90                   |
| PB 3000-P2-DD 6m | 1                    | 6                | 3000        | 90                   |
| PB 3000-P2-DD 8m | 1                    | 8                | 3000        | 90                   |
| PB 5000-P2-DD 2m | 1.5                  | 2                | 5000        | 150                  |
| PB 5000-P2-DD 3m | 1.5                  | 3                | 5000        | 150                  |
| PB 5000-P2-DD 4m | 1.5                  | 4                | 5000        | 150                  |
| PB 5000-P2-DD 5m | 1.5                  | 5                | 5000        | 150                  |
| PB 5000-P2-DD 6m | 1.5                  | 6                | 5000        | 150                  |
| PB 5000-P2-DD 8m | 1.5                  | 8                | 5000        | 150                  |

## ORDER NUMBERS

| End Fitting Component | WLL kg | 2 m     | 3 m     | 4 m     | 5 m     | 6 m     | 8 m     |
|-----------------------|--------|---------|---------|---------|---------|---------|---------|
| D-1000                | 1000   | 2025402 | 2025403 | 2025404 | 2025405 | 2025406 | 2025407 |
| D-2000                | 2000   | 2025408 | 2025409 | 2025410 | 2025411 | 2025412 | 2025413 |
| D-3000                | 3000   | 2025414 | 2025415 | 2025416 | 2025417 | 2025418 | 2025419 |
| D-4000                | 4000   | -       | -       | -       | -       | -       | -       |
| D-5000                | 5000   | 2025426 | 2025427 | 2025428 | 2025429 | 2025430 | 2025431 |



## PowerFlex with D-Rings

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

| End Fitting Component | WLL kg | 2 m | 3 m | 4 m | 5 m | 6 m | 8 m |
|-----------------------|--------|-----|-----|-----|-----|-----|-----|
| D-6000                | 6000   | -   | -   | -   | -   | -   | -   |

- Norms EN 1492-1: 2000
- Belt Layers 2
- Main Material Polyester
- Temperature Range -40°C bis +100°C
- Safety Factor 7:1
- Label Protection Yes
- Packaging Unit (PU) pcs
- Packaging Unit (PU) Content 1



## PowerFlex with D-Rings

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom