



SpanSet®

Height Safety
Lifting
Load Control
Safety Management

Product Name:
CLIMA Work Position Lanyard / Belt

Order Code:
5/2696—WPLANY 2M

What is it?
(Product Description):

The CLIMA Work Position Lanyard is a 2m lanyard CE Marked to EN358 and includes a twist-lock karabiner and an oval Maillon Rapide. A wear sleeve completes the lanyard which prevents, excessive wear, damage and cuts making it robust for passing over steel edges. This lanyard can support you in a hands-free position.

What can it be used for?

(Intended Function):

The CLIMA Work Position lanyard has been designed and tested to support a worker; this means that it is intended to be used as part of a Work Position System. The lanyard can be past around structural anchor points, clip to the harness belt and adjusted to support the user while they work. Simple locking action for easy one handed adjustment

What can I use with it? (Compatibility):

The CLIMA Work Position Lanyard is compatible with the following equipment and their associated systems;

- CLIMA harness
- ULTIMA harness
- EXCEL harness with belt
- 2-X harness with belt
- ATLAS harness with belt

If you are unsure of any equipment and its compatibility with the CLIMA Work Position Lanyard please contact SpanSet Ltd.

Who can use it?

(Competence, Size and Adjustment):

Work at height can be a high risk activity. It is therefore essential that all users are competent in the pre use inspection, fitting / adjustment and use of this item.

The CLIMA Work Position Lanyard has a maximum working length of 2m and can be reduced in length to 0.25m.

The CLIMA Work Position Lanyard is design to be used by 1 person. It can be used by any weight of person provided that it is used to prevent them falling. In this situation the maximum load place on the lanyard at any time should never exceed 1.5 times the user's weight.

How long will it last?

(Maintenance, Inspection and Lifespan):

The lifespan of the CLIMA Work Position Lanyard is limited by the following;

- The product has a maximum shelf-life of 10 years from the date of manufacture.

CLIMA Work Position Lanyard / Belt



- The product has a maximum service-life of 5 years from the date of first use.
 - The lifespan may also be reduced by the effects of damage or wear and tear. The lifespan will cease at the point when any one of these conditions is met.
- The condition of the product must be controlled in accordance with BS8437:2005, this requires regular inspections to be carried out by a competent person.

How has it been tested?

(Relevant Standard and Quality Assurance):

The CLIMA Work Position Lanyard is CE marked under the Personal Protective Equipment Directive. The CE marking process includes independent testing to EN358:2000 – Personal protective equipment for work positioning and prevention of falls from a height. Restraint and work positioning lanyards. The CE marking process includes independent testing to EN358:2000 – Personal protective equipment for work positioning and prevention of falls from a height. Restraint and work positioning lanyards. The SpanSet manufacturing process is quality controlled and audited by the British Standards Institute to the international standard for quality management ISO9001:2008.

What is it made from and why?

(Specification and Materials):

11mm Kernmantle Rope

- Supple to handle and easy to adjust
- Wear sleeve on rope for durability
- Sewn termination for simple inspection and maintenance

Alloy adjustment device

- Simple locking action for easy one handed adjustment

- Lightweight

Alloy Karabiner

- Twist-lock automatic locking gate for fast and safe connection to anchor points
- Captivated eye sewn into lanyard to ensure correct loading and prevent loss

Steel Maillon Rapide

- Threaded gate for secure connection to harness

- Durable and easy to inspect and maintain

Additional SpanSet Features:

Individual Serial Numbering – All SpanSet Height safety products are individually serial numbered for traceability.

What paperwork is supplied?

(Product Records and Information):

Individual Product History Card – This record card contains all the documentation required to maintain the product. The front forms the European Declaration of Conformity and the table on the reverse can be completed to form the inspection record.

Pocket Inspection Guide – This simple to follow pocket card identifies the key areas requiring inspection.

What training is required?

(Competency):

Although in itself this is a simple item to use, there are three stages that should be considered as part of the process as a whole. Training is available for all the stages outlined at the SpanSet training school in Middlewich or subject to suitability on a site of your choice:

Assessment and planning – Training Module 9 Management of Work At Height

Use – Training Module 1 Height Safety Equipment Appreciation and Inspection followed by an appropriate practical module.

Inspection and Maintenance – Training Module 1 and Module 7 Competent Person Practical Inspection & Record Keeping.

All training for work at height is conducted in accordance with BS8454:2006 and is audited as part of our ISO9001:2008 quality management system.

For additional information on training please go to www.spanset.co.uk or Email: training@spanset.co.uk

What if I need to know more?

(Further Information):

If you have any specific questions that have not been answered you should contact the SpanSet customer services department. Tel: 01606737494 Email: customerservices@spanset.co.uk