



Description Anneau de levage rotatif.

- Caractéristiques**
- Rotation à 360° ; sécurité quadruple.
 - À palier lisse, il s'oriente en fonction de la direction de la force.

- Conforme à**
- Norme EN1677-4

| Referencia | Rosca [M] | CMU [t] | Peso [kg] | A [mm] | B [mm] | C [mm] | D [Ø mm] | E [Ø mm] | F [mm] | K [Ø mm] | L [mm] | Ch [mm] |
|------------|--------------|------------|--------------|-----------|-----------|-----------|-------------|-------------|-----------|-------------|-----------|------------|
| XOPSR-08 | M08 | 0.3 | 0.12 | 35 | 11 | 9 | 25 | 25.5 | 30 | 46 | 12 | 6 |
| XOPSR-10 | M10 | 0.4 | 0.12 | 33.7 | 10 | 9.8 | 25 | 25.5 | 30 | 46 | 15 | 6 |
| XOPSR-12 | M12 | 0.75 | 0.2 | 41.5 | 12.5 | 11.5 | 30 | 30.6 | 36.5 | 55.5 | 18 | 8 |
| XOPSR-14 | M14 | 0.75 | 0.2 | 41.5 | 12.5 | 11.5 | 30 | 30.6 | 36.5 | 55.5 | 18 | 8 |
| XOPSR-16 | M16 | 1.5 | 0.35 | 49.5 | 14.5 | 15.7 | 35 | 36.5 | 42 | 64.5 | 24 | 10 |
| XOPSR-18 | M18 | 1.5 | 0.35 | 49.5 | 14.5 | 15.7 | 35 | 36.5 | 42 | 64.5 | 24 | 10 |
| XOPSR-20 | M20 | 2.3 | 0.6 | 58 | 16 | 18 | 40 | 42 | 52.5 | 74.5 | 30 | 12 |
| XOPSR-22 | M22 | 2.3 | 0.6 | 58 | 16 | 18 | 40 | 42 | 52.5 | 74.5 | 30 | 12 |
| XOPSR-24 | M24 | 3.2 | 1 | 69 | 20.5 | 22 | 49 | 50 | 61 | 90 | 36 | 12 |
| XOPSR-27 | M27 | 3.2 | 1 | 69 | 20.5 | 22 | 49 | 50 | 61 | 90 | 36 | 12 |
| XOPSR-30 | M30 | 4.5 | 2 | 86 | 25.5 | 28 | 60 | 66 | 75 | 111 | 45 | 17 |
| XOPSR-33 | M33 | 4.5 | 2 | 86 | 25.5 | 28 | 60 | 66 | 75 | 111 | 45 | 17 |
| XOPSR-36 | M36 | 7 | 3.4 | 105 | 32 | 30 | 74 | 77 | 96.5 | 135 | 55 | 22 |
| XOPSR-42 | M42 | 9 | 5.7 | 118 | 38 | 37 | 82 | 87 | 110 | 158 | 65 | 24 |
| XOPSR-48 | M48 | 12 | 8.5 | 137 | 43 | 38 | 95 | 102 | 124.5 | 180 | 72 | 27 |

EN1677-4

SpanSet SARL

Tél. 04 72 47 69 90

Fax. 04 72 47 00 19

Email commercial@spanset.fr

www.spanset.fr