

GRABBA LIFTING BAG

Height Safety Lifting Load Control Safety Management

User Instructions



MANUFACTURED BY:

SPANSET LTD Telford Way, Middlewich, Cheshire, CW10 0HX

Tel: +44(0)1606 737494 Fax: +44(0)1606 737 264

www.spanset.co.uk



GRABBA LIFTING BAG

Height Safety Lifting Load Control Safety Management

Grabba Lifting bags are a lifting accessory designed to provide a convenient method of lifting tools and equipment in a water resistant containment bag in complete safety.

The Grabba bag allows workers to load tools and materials into a safe containment bag and lift them in compliance with lifting regulations and LOLER.

The Grabba bag comes in 3 sizes Small - 75Kg SWL; Medium – 125Kg SWL; Large 250Kg SWL



WARNING

The misuse of this equipment could lead to injury or death.

All lifting operations must be properly planned and risk assessed.

Lifting operations should only be performed by a competent person.

This equipment is not designed for lifting or suspension of persons.

Do not exceed the working load limit of this equipment.

LIMITATIONS

Grabba lifting bags are designed to provide a convenient method of lifting loose tools or materials within the confines of the bag.

The Grabba bag should only be used for lifting in tandem with a maximum of two Grabba bags linked together.

Lifting appliances should only be attached to the oval metal masterlink or to both of the purple lifting handles as described in the instructions. Do not attach any lifting appliance to the metal D link in the base of the bag.



GRABBA LIFTING BAG

Height Safety Lifting Load Control Safety Management

Using the Grabba Bag

- 1. Prior to use check the condition of the sling on the bag.
- Open the bag and place equipment or material inside.Roll the top of the bag and clip the two ends together to close the bag.
- 3. Secure the lifting appliance to the metal masterlink or to both of the purple lifting handles.
- 4. Conduct a trial lift, raising the Grabba Bag so that it is just clear of the floor. Ensure that it is secure and orientated appropriately.
- 5. If required a second Grabba Bag of the same size may be attached below the first Grabba bag by linking the metal D Link on the base of the top bag to the metal masterlink on the second bag using a 2t rated shackle.
- 6. Stand clear from underneath the load as it is lifted, lowered or suspended at height. **Inspection and Examination**

The Grabba Bag is a lifting accessory and should be examined at least once every six months by a competent person or in accordance with statutory requirements.

Prior to each use the sling should be checked for defects and damage:

Check the label, and that the information is legible.

Check the condition of the plastic heat shrunk cover protecting the label and the stitching. It should be intact.

Check the webbing components for signs of:

- · Cuts and abrasions.
- Signs of degradation from exposure to chemicals, heat and UV.