



Lashing Configuration
Carlash



ABS 5000daN 50mm

Transport heavy loads safely with progressive release, for safe release of tension and no load tipping

Item Name short	Colour	Dimension L3 [m]	Lashing End Fitting Component	Surface Coating	Weight Net [kg]
ABS LC5000/50 carlash 4m CL	Metallic	-	-	no	-
ABS LC5000/50 carlash 4m CL b	Metallic	-	-	Epoxy	-
ABS LC5000/50 carlash 4m DD	Blue	3.5	DD-50	no	3.9
ABS LC5000/50 carlash 4m DD b	Blue	3.5	DD-50	Epoxy	3.9
ABS LC5000/50 carlash 4m DH b	Blue	3.5	DH-50	Epoxy	5.4
ABS LC5000/50 carlash 4m DH	Blue	3.5	DH-50	Chromated	5.4
ABS LC5000/50 carlash 4m CSH b	Blue	-	CSH-50	Epoxy	-
ABS LC5000/50 carlash 4m CSH	Blue	-	CSH-50	no	-

ORDER NUMBERS

Lashing End Fitting Component	333	563	1266
DD-50	2003502	-	2004016
DH-50	-	2004013	2004017
CSH-50	2003006	-	2004014

■ Norms	EN 12195-2: 2001
■ Webbing Material	Polyester, thermofixed and low-stretch <4%
■ Webbing Width B	50 mm
■ Quality	professional
■ Anti Belt Slip (ABS)	Yes
■ Label Protection	Yes
■ Handle Type	Standard
■ Private Label	Yes

ABS 5000/50

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

