



Magnum-X

Extremely slim and easy to handle heavy duty lifting sling ideal for small crane hooks

Item Name short	Colour	Contact Thickness Under Load [mm]	Contact Width Under Load [mm]	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	WLL t [t]
Magnum-X 5 t 2m	Red	6	36	1.0	2	5000	5
Magnum-X 5 t 3m	Red	6	36	1.0	3	5000	5
Magnum-X 5000 4m	Red	6	36	1.0	4	5000	5
Magnum-X 5000 5m	Red	6	36	1.0	5	5000	5
Magnum-X 5000 6m	Red	6	36	1.0	6	5000	5
Magnum-X 5000 7m	Red	6	36	1.0	7	5000	5
Magnum-X 5000 8m	Red	6	36	1.0	8	5000	5
Magnum-X 5 t 10m	Red	6	36	1.0	10	5000	5
Magnum-X 5 t 12m	Red	6	36	1.0	12	5000	5
Magnum-X 10000 2m	Orange	12	65	2	2	10000	10
Magnum-X 10000 2.5m	Orange	12	65	2	2.5	10000	10
Magnum-X 10000 3m	Orange	12	65	2	3	10000	10
Magnum-X 10000 4m	Orange	12	65	2	4	10000	10
Magnum-X 10000 5m	Orange	12	65	2	5	10000	10
Magnum-X 10000 6m	Orange	12	65	2	6	10000	10
Magnum-X 10000 7m	Orange	12	65	2	7	10000	10
Magnum-X 10000 8m	Orange	12	65	2	8	10000	10
Magnum-X 10000 10m	Orange	12	65	2	10	10000	10
Magnum-X 10000 12m	Orange	12	65	2	12	10000	10
Magnum-X 30000 2m	Orange	18	101	2	2	30000	30



Magnum-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Item Name short	Colour	Contact Thickness Under Load [mm]	Contact Width Under Load [mm]	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	WLL t [t]
Magnum-X 30000 2.5m	Orange	18	101	2	2.5	30000	30
Magnum-X 30000 3m	Orange	18	101	2	3	30000	30
Magnum-X 30000 4m	Orange	18	101	2	4	30000	30
Magnum-X 30000 5m	Orange	18	101	2	5	30000	30
Magnum-X 30000 6m	Orange	18	101	2	6	30000	30
Magnum-X 30000 7m	Orange	18	101	2	7	30000	30
Magnum-X 30000 8m	Orange	18	101	2	8	30000	30
Magnum-X 30000 9m	Orange	18	101	2	9	30000	30
Magnum-X 30000 10m	Orange	18	101	2	10	30000	30
Magnum-X 30000 12m	Orange	18	101	2	12	30000	30
Magnum-X 20000 2m	Orange	19	67	2	2	20000	20
Magnum-X 20000 2.5m	Orange	19	67	2	2.5	20000	20
Magnum-X 20000 3m	Orange	19	67	2	3	20000	20
Magnum-X 20000 4m	Orange	19	67	2	4	20000	20
Magnum-X 20000 5m	Orange	19	67	2	5	20000	20
Magnum-X 20000 6m	Orange	19	67	2	6	20000	20
Magnum-X 20000 7m	Orange	19	67	2	7	20000	20
Magnum-X 20000 8m	Orange	19	67	2	8	20000	20
Magnum-X 20000 10m	Orange	19	67	2	10	20000	20
Magnum-X 20000 12m	Orange	19	67	2	12	20000	20
Magnum-X 25000 4m	Orange	19	85	2	4	25000	25



Magnum-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Item Name short	Colour	Contact Thickness Under Load [mm]	Contact Width Under Load [mm]	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	WLL t [t]
Magnum-X 25000 5m	Orange	19	85	2	5	25000	25
Magnum-X 25000 6m	Orange	19	85	2	6	25000	25
Magnum-X 25000 7m	Orange	19	85	2	7	25000	25
Magnum-X 25000 8m	Orange	19	85	2	8	25000	25
Magnum-X 50000 3m	Orange	19	146	2	3	50000	50
Magnum-X 50000 4m	Orange	19	146	2	4	50000	50
Magnum-X 50000 5m	Orange	19	146	2	5	50000	50
Magnum-X 50000 6m	Orange	19	146	2	6	50000	50
Magnum-X 50000 7m	Orange	19	146	2	7	50000	50
Magnum-X 50000 8m	Orange	19	146	2	8	50000	50
Magnum-X 50000 10m	Orange	19	146	2	10	50000	50
Magnum-X 50000 12m	Orange	19	146	2	12	50000	50
Magnum-X 50000 13m	Orange	19	146	2	13	50000	50
Magnum-X 60000 4m	Orange	21	173	3	4	60000	60
Magnum-X 60000 5m	Orange	21	173	3	5	60000	60
Magnum-X 60000 6m	Orange	21	173	3	6	60000	60
Magnum-X 60000 7m	Orange	21	173	3	7	60000	60
Magnum-X 60000 8m	Orange	21	173	3	8	60000	60
Magnum-X 60000 10m	Orange	21	173	3	10	60000	60
Magnum-X 60000 12m	Orange	21	173	3	12	60000	60
Magnum-X 80000 4m	Orange	24	192	3	4	80000	80



Magnum-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Item Name short	Colour	Contact Thickness Under Load [mm]	Contact Width Under Load [mm]	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	WLL t [t]
Magnum-X 80000 5m	Orange	24	192	3	5	80000	80
Magnum-X 80000 6m	Orange	24	192	3	6	80000	80
Magnum-X 80000 7m	Orange	24	192	3	7	80000	80
Magnum-X 80000 8m	Orange	24	192	3	8	80000	80
Magnum-X 80 t 10m	Orange	24	192	3	10	80000	80
Magnum-X 80 t 12m	Orange	24	192	3	12	80000	80
Magnum-X 40000 2.5m	Orange	25	105	2	2.5	40000	40
Magnum-X 40000 3m	Orange	25	105	2	3	40000	40
Magnum-X 40000 4m	Orange	25	105	2	4	40000	40
Magnum-X 40000 5m	Orange	25	105	2	5	40000	40
Magnum-X 40000 6m	Orange	25	105	2	6	40000	40
Magnum-X 40000 7m	Orange	25	105	2	7	40000	40
Magnum-X 40000 8m	Orange	25	105	2	8	40000	40
Magnum-X 40000 10m	Orange	25	105	2	10	40000	40
Magnum-X 40000 12m	Orange	25	105	2	12	40000	40
Magnum-X 100000 4m	Orange	35	227	3	4	100000	100
Magnum-X 100000 5m	Orange	35	227	3	5	100000	100
Magnum-X 100000 6m	Orange	35	227	3	6	100000	100
Magnum-X 100000 7m	Orange	35	227	3	7	100000	100
Magnum-X 100000 8m	Orange	35	227	3	8	100000	100
Magnum-X 100 t 10m	Orange	35	227	3	10	100000	100



Magnum-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Item Name short	Colour	Contact Thickness Under Load [mm]	Contact Width Under Load [mm]	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	WLL t [t]
Magnum-X 100 t 12m	Orange	35	227	3	12	100000	100
Magnum-X 125000 4m	Orange	39	300	3	4	125000	125
Magnum-X 125000 5m	Orange	39	300	3	5	125000	125
Magnum-X 125000 6m	Orange	39	300	3	6	125000	125
Magnum-X 125000 7m	Orange	39	300	3	7	125000	125
Magnum-X 125000 8m	Orange	39	300	3	8	125000	125
Magnum-X 125 t 10m	Orange	39	300	3	10	125000	125
Magnum-X 125 t 12m	Orange	39	300	3	12	125000	125
Magnum-X 150000 4m	Orange	51	280	5	4	150000	150
Magnum-X 150000 5m	Orange	51	280	5	5	150000	150
Magnum-X 150000 6m	Orange	51	280	5	6	150000	150
Magnum-X 150000 7m	Orange	51	280	5	7	150000	150
Magnum-X 150000 8m	Orange	51	280	5	8	150000	150
Magnum-X 150 t 10m	Orange	51	280	5	10	150000	150
Magnum-X 150 t 12m	Orange	51	280	5	12	150000	150

Item Name short	Weight Net [kg]	Weight per Meter [kg/m]
Magnum-X 5 t 2m	0.94	0.47
Magnum-X 5 t 3m	1.41	0.47
Magnum-X 5000 4m	1.88	0.47
Magnum-X 5000 5m	2.35	0.47
Magnum-X 5000 6m	2.82	0.47
Magnum-X 5000 7m	3.29	0.47



Magnum-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Item Name short	Weight Net [kg]	Weight per Meter [kg/m]
Magnum-X 5000 8m	3.76	0.47
Magnum-X 5 t 10m	4.7	0.47
Magnum-X 5 t 12m	5.64	0.47
Magnum-X 10000 2m	1.8	0.9
Magnum-X 10000 2.5m	2.25	0.9
Magnum-X 10000 3m	2.7	0.9
Magnum-X 10000 4m	4.1	0.9
Magnum-X 10000 5m	5	0.9
Magnum-X 10000 6m	5.9	0.9
Magnum-X 10000 7m	6.8	0.9
Magnum-X 10000 8m	7.7	0.9
Magnum-X 10000 10m	9.5	0.9
Magnum-X 10000 12m	10.8	0.9
Magnum-X 30000 2m	-	3.27
Magnum-X 30000 2.5m	5.75	3.27
Magnum-X 30000 3m	6.9	3.27
Magnum-X 30000 4m	12.1	3.27
Magnum-X 30000 5m	15	3.27
Magnum-X 30000 6m	17.9	3.27
Magnum-X 30000 7m	20.8	3.27
Magnum-X 30000 8m	23.7	3.27
Magnum-X 30000 9m	20.7	3.27
Magnum-X 30000 10m	29.5	3.27
Magnum-X 30000 12m	27.6	3.27
Magnum-X 20000 2m	3.6	1.8
Magnum-X 20000 2.5m	4.5	1.8
Magnum-X 20000 3m	5.4	1.8
Magnum-X 20000 4m	7.7	1.8
Magnum-X 20000 5m	9.5	1.8
Magnum-X 20000 6m	11.3	1.8
Magnum-X 20000 7m	13.1	1.8
Magnum-X 20000 8m	14.9	1.8
Magnum-X 20000 10m	18.5	1.8



Magnum-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Item Name short	Weight Net [kg]	Weight per Meter [kg/m]
Magnum-X 20000 12m	21.6	1.8
Magnum-X 25000 4m	10.1	2.4
Magnum-X 25000 5m	12.5	2.4
Magnum-X 25000 6m	14.9	2.4
Magnum-X 25000 7m	17.3	2.4
Magnum-X 25000 8m	19.7	2.4
Magnum-X 50000 3m	15.6	5.2
Magnum-X 50000 4m	21.3	5.2
Magnum-X 50000 5m	26.5	5.2
Magnum-X 50000 6m	31.7	5.2
Magnum-X 50000 7m	36.9	5.2
Magnum-X 50000 8m	42.1	5.2
Magnum-X 50000 10m	52.5	5.2
Magnum-X 50000 12m	62.4	5.2
Magnum-X 50000 13m	-	5.2
Magnum-X 60000 4m	28.9	5.8
Magnum-X 60000 5m	36	5.8
Magnum-X 60000 6m	43.1	5.8
Magnum-X 60000 7m	50.2	5.8
Magnum-X 60000 8m	57.3	5.8
Magnum-X 60000 10m	71.5	5.8
Magnum-X 60000 12m	69.6	5.8
Magnum-X 80000 4m	38.1	8.2
Magnum-X 80000 5m	47.5	8.2
Magnum-X 80000 6m	56.9	8.2
Magnum-X 80000 7m	66.3	8.2
Magnum-X 80000 8m	75.7	8.2
Magnum-X 80 t 10m	94.5	8.2
Magnum-X 80 t 12m	98.4	8.2
Magnum-X 40000 2.5m	8.75	3.5
Magnum-X 40000 3m	10.5	3.5
Magnum-X 40000 4m	16.1	3.5
Magnum-X 40000 5m	20	3.5



Magnum-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Item Name short	Weight Net [kg]	Weight per Meter [kg/m]
Magnum-X 40000 6m	23.9	3.5
Magnum-X 40000 7m	27.8	3.5
Magnum-X 40000 8m	31.7	3.5
Magnum-X 40000 10m	39.5	3.5
Magnum-X 40000 12m	42	3.5
Magnum-X 100000 4m	54.9	11.8
Magnum-X 100000 5m	68.5	11.8
Magnum-X 100000 6m	82.1	11.8
Magnum-X 100000 7m	95.7	11.8
Magnum-X 100000 8m	109.3	11.8
Magnum-X 100 t 10m	136.5	11.8
Magnum-X 100 t 12m	141.6	11.8
Magnum-X 125000 4m	75.3	18.7
Magnum-X 125000 5m	94	18.7
Magnum-X 125000 6m	112.7	18.7
Magnum-X 125000 7m	131.4	18.7
Magnum-X 125000 8m	150.1	18.7
Magnum-X 125 t 10m	187.5	18.7
Magnum-X 125 t 12m	224.4	18.7
Magnum-X 150000 4m	80.5	20
Magnum-X 150000 5m	100.5	20
Magnum-X 150000 6m	120.5	20
Magnum-X 150000 7m	140.5	20
Magnum-X 150000 8m	160.5	20
Magnum-X 150 t 10m	200.5	20
Magnum-X 150 t 12m	240	20



Magnum-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

ORDER NUMBERS

Dimension L1	5000 kg	10000 kg	20000 kg	25000 kg	30000 kg	40000 kg	50000 kg	60000 kg	80000 kg	100000 kg	125000 kg
2	2025045	2026603	2026604	-	2017500	-	-	-	-	-	-
2.5	-	2020987	2020991	-	2020993	2020995	-	-	-	-	-
3	2026602	2020989	2020992	-	2020994	2020996	2024598	-	-	-	-
4	2010959	2002763	2002765	2002767	2002769	2002771	2002773	2002775	2002777	2002779	2002781
5	2010960	2002764	2002766	2002768	2002770	2002772	2002774	2002776	2002778	2002780	2002782
6	2010961	2003251	2003253	2003255	2003257	2003259	2003261	2003263	2003265	2003267	2003269
7	2010962	2003252	2003254	2003256	2003258	2003260	2003262	2003264	2003266	2003268	2003270
8	2010963	2003738	2003739	2003740	2003741	2003742	2003743	2003744	2003745	2003746	2003747
9	-	-	-	-	2014794	-	-	-	-	-	-
10	2014758	2014760	2014762	-	2014765	2014767	2014769	2014771	2014773	2014775	2014777
12	2014759	2014761	2014763	-	2014766	2014768	2014770	2014772	2014774	2014776	2014778
13	-	-	-	-	-	-	2021245	-	-	-	-

Dimension L1	150000 kg
2	-
2.5	-
3	-
4	2002783
5	2002784
6	2003271
7	2003272
8	2003748
9	-
10	2014779
12	2014780
13	-

- Norms EN 1492-2: 2000
- Main Material High-performance polyester
- Dimension L1 max 30 m
- Temperature Range - 40 bis + 100°C
- Safety Factor 7:1
- Sideseam Yes
- Label Protection Yes
- Packaging Unit (PU) pcs

SpanSet (UK) Limited
Telford Way Middlewich
Cheshire CW10 0HX
United Kingdom
Tel.: +44 (0) 1606
737494
info@spanset.co.uk
www.spanset.co.uk



Magnum-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

SpanSet
Certified
Safety

■ Packaging Unit (PU) Content 1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

**Magnum-X**

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom