

TECHNICAL DATASHEET

Height SafetyManhole guard with integrated mast EN 795: 2012 AS/NZS 5532

01



Manhole guard with integrated mast

Davit arm for regular surfaces in transit areas where access must be restricted

Item Name short	Accessories
XT-2	-
XT-2-ST	XT-A2108-18
XT-2-STW	XT-A2108-20

ORDER NUMBERS

Accessories	XT-2	XT-2-ST	XT-2-STW
XT-A2108-18	-	2029782	-
XT-A2108-20	-	-	2029908

Arm Reach 610

■ Norms EN 795: 2012 AS/NZS 5532

ColourYellowMain MaterialAluminiumArm Reach381 - 610 mm

■ Working angle 0°
■ Load Capacity (kg) 191 kg

SpanSet (UK) Limited Telford Way Middlewich Cheshire CW10 0HX United Kingdom Tel.: +44 (0) 1606 737494 info@spanset.co.uk www.spanset.co.uk



Manhole Guard System

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom