



MaXafe 5000daN 55mm

High resistant webbing lashing strap, ideal for transverse and diagonal lashing of heavy vehicles and machines

Item Name short	Dimension L1 [m]	Lashing End Fitting Component	Weight Net [kg]
MaXafe LC5000/55 2pc 3m DJHS	3	DJHS-50	4.50
MaXafe LC5000/55 2pc 3m DH	3	DH-50	6.50
MaXafe LC5000/55 2pc 4m DJHS	4	DJHS-50	4.70
MaXafe LC5000/55 2pc 4m DH	4	DH-50	6.70

Lashing Configuration

2-Piece



ORDER NUMBERS

Lashing End Fitting Component	3	4
DJHS-50	2005985	2005986
DH-50	2005988	2005989

■ Norms	EN 12195-2: 2001
■ Surface Coating	Epoxy
■ Colour	Green
■ Webbing Material	High-performance webbing low expansion <2 %
■ Webbing Width B	55 mm
■ Quality	professional
■ Anti Belt Slip (ABS)	No
■ Label Protection	Yes
■ Handle Type	Long Wide
■ Private Label	Yes



MaXafe 5000/55

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom