



### PowerFlex Abrasion resistance full coated lifting sling

Item Name short	Colour	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	WLL t [t]	Webbing Width B [mm]	Weight Net [kg]
PB 2000-P2 1.25m	Green	1	1.25	2000	2	60	1.2
PB 1000-P2 2m	Purple	1	2	1000	1	30	0.7
PB 2000-P2 2m	Green	1	2	2000	2	60	1.6
PB 2000-P2 2.5m	Green	1	2.5	2000	2	60	1.9
PB 1000-P2 3m	Purple	1	3	1000	1	30	1
PB 2000-P2 3m	Green	1	3	2000	2	60	2.2
PB 1000-P2 4m	Purple	1	4	1000	1	30	1.3
PB 2000-P2 4m	Green	1	4	2000	2	60	2.8
PB 1000-P2 5m	Purple	1	5	1000	1	30	1.6
PB 2000-P2 5m	Green	1	5	2000	2	60	3.4
PB 1000-P2 6m	Purple	1	6	1000	1	30	1.9
PB 2000-P2 6m	Green	1	6	2000	2	60	4
PB 2000-P2 7m	Green	1	7	2000	2	60	4.5
PB 3000-P2 2m	Yellow	1.3	2	3000	3	90	2.1
PB 4000-P2 2m	Grey	1.3	2	4000	4	120	2.9
PB 3000-P2 3m	Yellow	1.3	3	3000	3	90	2.9
PB 4000-P2 3m	Grey	1.3	3	4000	4	120	4
PB 3000-P2 4m	Yellow	1.3	4	3000	3	90	3.7
PB 4000-P2 4m	Grey	1.3	4	4000	4	120	5.1
PB 3000-P2 5m	Yellow	1.3	5	3000	3	90	4.5



### PowerFlex P2

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Item Name short	Colour	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	WLL t [t]	Webbing Width B [mm]	Weight Net [kg]
PB 4000-P2 5m	Grey	1.3	5	4000	4	120	6.2
PB 3000-P2 6m	Yellow	1.3	6	3000	3	90	5.3
PB 4000-P2 6m	Grey	1.3	6	4000	4	120	7.3
PB 5000-P2 2m	Red	1.5	2	5000	5	150	3.8
PB 5000-P2 3m	Red	1.5	3	5000	5	150	5.2
PB 5000-P2 4m	Red	1.5	4	5000	5	150	6.6
PB 5000-P2 5m	Red	1.5	5	5000	5	150	8
PB 5000-P2 6m	Red	1.5	6	5000	5	150	9.4

### ORDER NUMBERS

Dimension L1	End Fitting Component	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg
1.25	-	-	2015461	-	-	-
2	-	2015456	2015462	2015469	2015474	2015479
2.5	-	-	2015463	-	-	-
3	-	2015457	2015464	2015470	2015475	2015480
4	-	2015458	2015465	2015471	2015476	2015481
5	-	2015459	2015466	2015472	2015477	2015482
6	-	2015460	2015467	2015473	2015478	2015483
7	-	-	2015468	-	-	-

■ Norms	EN 1492-1: 2000
■ End Fitting Component	-
■ Belt Layers	2
■ Main Material	Polyester
■ Temperature Range	-40°C bis +100°C
■ Safety Factor	7:1
■ Label Protection	Yes
■ Packaging Unit (PU)	pcs
■ Packaging Unit (PU) Content	1



## PowerFlex P2

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom