



Secutex S2

Cut-resistant full coated flat sling, Nearly indestructible!

Item Name short	Colour	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	Webbing Thickness [mm]	Webbing Width B [mm]	Weight Net [kg]
PB 1000-S2 2m	Purple	1	2	1000	17.1	30	0.9
PB 2000-S2 2m	Green	1	2	2000	17.5	60	2
PB 1000-S2 3m	Purple	1	3	1000	17.1	30	1.3
PB 2000-S2 3m	Green	1	3	2000	17.5	60	2.8
PB 1000-S2 4m	Purple	1	4	1000	17.1	30	1.7
PB 2000-S2 4m	Green	1	4	2000	17.5	60	3.6
PB 1000-S2 5m	Purple	1	5	1000	17.1	30	2.1
PB 2000-S2 5m	Green	1	5	2000	17.5	60	4.4
PB 1000-S2 6m	Purple	1	6	1000	17.1	30	2.5
PB 2000-S2 6m	Green	1	6	2000	17.5	60	5.2
PB 2000-S2 8m	Green	1	8	2000	17.5	60	6.8
PB 3000-S2 2m	Yellow	1.3	2	3000	17.9	90	2.9
PB 4000-S2 2m	Grey	1.3	2	4000	18.9	120	4
PB 3000-S2 3m	Yellow	1.3	3	3000	17.9	90	4.2
PB 4000-S2 3m	Grey	1.3	3	4000	18.9	120	5.8
PB 3000-S2 4m	Yellow	1.3	4	3000	17.9	90	5.5
PB 4000-S2 4m	Grey	1.3	4	4000	18.9	120	7.6
PB 3000-S2 5m	Yellow	1.3	5	3000	17.9	90	6.8
PB 4000-S2 5m	Grey	1.3	5	4000	18.9	120	9.4
PB 3000-S2 6m	Yellow	1.3	6	3000	17.9	90	8.1



Secutex S2 with Loops

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Item Name short	Colour	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	Webbing Thickness [mm]	Webbing Width B [mm]	Weight Net [kg]
PB 4000-S2 6m	Grey	1.3	6	4000	18.9	120	11.2
PB 3000-S2 7m	Yellow	1.3	7	3000	17.9	90	9.4
PB 5000-S2 2m	Red	1.5	2	5000	18.9	150	5
PB 5000-S2 3m	Red	1.5	3	5000	18.9	150	7.2
PB 5000-S2 4m	Red	1.5	4	5000	18.9	150	9.4
PB 5000-S2 5m	Red	1.5	5	5000	18.9	150	11.6
PB 5000-S2 6m	Red	1.5	6	5000	18.9	150	13.8
PB 5000-S2 8m	Red	1.5	8	5000	18.9	150	27.5
PB 6000-S2 2m	Brown	1.9	2	6000	19.1	180	6
PB 6000-S2 3m	Brown	1.9	3	6000	19.1	180	8.7
PB 6000-S2 4m	Brown	1.9	4	6000	19.1	180	11.4
PB 6000-S2 5m	Brown	1.9	5	6000	19.1	180	14.1
PB 6000-S2 6m	Brown	1.9	6	6000	19.1	180	16.8
PB 6000-S2 8m	Brown	1.9	8	6000	19.1	180	31
PB 8000-S2 3m	Blue	2.2	3	8000	19.1	250	12.8
PB 8000-S2 4m	Blue	2.2	4	8000	19.1	250	16.9
PB 8000-S2 5m	Blue	2.2	5	8000	19.1	250	21
PB 8000-S2 6m	Blue	2.2	6	8000	19.1	250	25.1
PB 8000-S2 8m	Blue	2.2	8	8000	19.1	250	33.3



Secutex S2 with Loops

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Item Name short	Weight for 1m [kg]	Weight per Meter [kg/m]
PB 1000-S2 2m	0.9	0.8
PB 2000-S2 2m	1.4	1.4
PB 1000-S2 3m	0.9	0.8
PB 2000-S2 3m	1.4	1.4
PB 1000-S2 4m	0.9	0.8
PB 2000-S2 4m	1.4	1.4
PB 1000-S2 5m	0.9	0.8
PB 2000-S2 5m	1.4	1.4
PB 1000-S2 6m	0.9	0.8
PB 2000-S2 6m	1.4	1.4
PB 2000-S2 8m	1.4	1.4
PB 3000-S2 2m	2.1	2
PB 4000-S2 2m	2.9	2.7
PB 3000-S2 3m	2.1	2
PB 4000-S2 3m	2.9	2.7
PB 3000-S2 4m	2.1	2
PB 4000-S2 4m	2.9	2.7
PB 3000-S2 5m	2.1	2
PB 4000-S2 5m	2.9	2.7
PB 3000-S2 6m	2.1	2
PB 4000-S2 6m	2.9	2.7
PB 3000-S2 7m	2.1	2
PB 5000-S2 2m	3.7	3.4
PB 5000-S2 3m	3.7	3.4
PB 5000-S2 4m	3.7	3.4
PB 5000-S2 5m	3.7	3.4
PB 5000-S2 6m	3.7	3.4
PB 5000-S2 8m	3.7	3.4
PB 6000-S2 2m	4.4	3.8
PB 6000-S2 3m	4.4	3.8
PB 6000-S2 4m	4.4	3.8
PB 6000-S2 5m	4.4	3.8
PB 6000-S2 6m	4.4	3.8



Secutex S2 with Loops

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Item Name short	Weight for 1m [kg]	Weight per Meter [kg/m]
PB 6000-S2 8m	4.4	3.8
PB 8000-S2 3m	4.6	4.1
PB 8000-S2 4m	4.6	4.1
PB 8000-S2 5m	4.6	4.1
PB 8000-S2 6m	4.6	4.1
PB 8000-S2 8m	4.6	4.1

ORDER NUMBERS

WLL kg	2 m	3 m	4 m	5 m	6 m	7 m	8 m
1000	2015425	2015426	2015427	2015428	2015429	-	-
2000	2015430	2015431	2015432	2015433	2015434	-	2015435
3000	2015436	2015437	2015438	2015439	2015440	2015441	-
4000	2015442	2015443	2015444	2015445	2015446	-	-
5000	2015447	2015448	2015449	2015450	2015451	-	2018503
6000	2015452	2015453	2015454	2015455	2017065	-	2018504
8000	-	2018505	2018506	2018507	2018508	-	2018509

■ Norms	EN 1492-1: 2000
■ Belt Layers	2
■ Main Material	Polyester
■ Temperature Range	-40°C bis +100°C
■ Safety Factor	7:1
■ Label Protection	Yes
■ Packaging Unit (PU)	pcs
■ Packaging Unit (PU) Content	1



Secutex S2 with Loops

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom