



SupraPlus-X

Durable and compact design lifting sling with protected label ensures reliable performance and extended service life

| Item Name short | Colour | Contact Thickness Under Load [mm] | Contact Width Under Load [mm] | Dimension L1 min [m] | Dimension L1 [m] | WLL kg [kg] | WLL t [t] |
|------------------------|--------|-----------------------------------|-------------------------------|----------------------|------------------|-------------|-----------|
| SupraPlus-X 500 0.5m | Olive | 4 | 38 | 0.5 | 0.5 | 500 | 0.5 |
| SupraPlus-X 500 0.75m | Olive | 4 | 38 | 0.5 | 0.75 | 500 | 0.5 |
| SupraPlus-X 500 1.0m | Olive | 4 | 38 | 0.5 | 1 | 500 | 0.5 |
| SupraPlus-X 500 1.5m | Olive | 4 | 38 | 0.5 | 1.5 | 500 | 0.5 |
| SupraPlus-X 500 2.0m | Olive | 4 | 38 | 0.5 | 2 | 500 | 0.5 |
| SupraPlus-X 500 2.5m | Olive | 4 | 38 | 0.5 | 2.5 | 500 | 0.5 |
| SupraPlus-X 500 3.0m | Olive | 4 | 38 | 0.5 | 3 | 500 | 0.5 |
| SupraPlus-X 500 5.0m | Olive | 4 | 38 | 0.5 | 5 | 500 | 0.5 |
| SupraPlus-X 1000 0.5m | Purple | 4 | 39 | 0.5 | 0.5 | 1000 | 1 |
| SupraPlus-X 1000 0.75m | Purple | 4 | 39 | 0.5 | 0.75 | 1000 | 1 |
| SupraPlus-X 1000 1.0m | Purple | 4 | 39 | 0.5 | 1 | 1000 | 1 |
| SupraPlus-X 1000 1.5m | Purple | 4 | 39 | 0.5 | 1.5 | 1000 | 1 |
| SupraPlus-X 1000 2.0m | Purple | 4 | 39 | 0.5 | 2 | 1000 | 1 |
| SupraPlus-X 1000 2.5m | Purple | 4 | 39 | 0.5 | 2.5 | 1000 | 1 |
| SupraPlus-X 1000 3.0m | Purple | 4 | 39 | 0.5 | 3 | 1000 | 1 |
| SupraPlus-X 1000 4.0m | Purple | 4 | 39 | 0.5 | 4 | 1000 | 1 |
| SupraPlus-X 1000 5.0m | Purple | 4 | 39 | 0.5 | 5 | 1000 | 1 |
| SupraPlus-X 1000 6.0m | Purple | 4 | 39 | 0.5 | 6 | 1000 | 1 |
| SupraPlus-X 1000 10m | Purple | 4 | 39 | 0.5 | 10 | 1000 | 1 |



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

| Item Name short | Colour | Contact Thickness Under Load [mm] | Contact Width Under Load [mm] | Dimension L1 min [m] | Dimension L1 [m] | WLL kg [kg] | WLL t [t] |
|------------------------|--------|-----------------------------------|-------------------------------|----------------------|------------------|-------------|-----------|
| SupraPlus-X 2000 0.5m | Green | 8 | 40 | 0.5 | 0.5 | 2000 | 2 |
| SupraPlus-X 2000 0.75m | Green | 8 | 40 | 0.5 | 0.75 | 2000 | 2 |
| SupraPlus-X 2000 1.0m | Green | 8 | 40 | 0.5 | 1 | 2000 | 2 |
| SupraPlus-X 2000 1.5m | Green | 8 | 40 | 0.5 | 1.5 | 2000 | 2 |
| SupraPlus-X 2000 2.0m | Green | 8 | 40 | 0.5 | 2 | 2000 | 2 |
| SupraPlus-X 2000 2.5m | Green | 8 | 40 | 0.5 | 2.5 | 2000 | 2 |
| SupraPlus-X 2000 3.0m | Green | 8 | 40 | 0.5 | 3 | 2000 | 2 |
| SupraPlus-X 2000 4.0m | Green | 8 | 40 | 0.5 | 4 | 2000 | 2 |
| SupraPlus-X 2000 5.0m | Green | 8 | 40 | 0.5 | 5 | 2000 | 2 |
| SupraPlus-X 2000 6.0m | Green | 8 | 40 | 0.5 | 6 | 2000 | 2 |
| SupraPlus-X 2000 7.0m | Green | 8 | 40 | 0.5 | 7 | 2000 | 2 |
| SupraPlus-X 2000 8.0m | Green | 8 | 40 | 0.5 | 8 | 2000 | 2 |
| SupraPlus-X 3000 0.5m | Yellow | 8 | 48 | 0.5 | 0.5 | 3000 | 3 |
| SupraPlus-X 3000 1.0m | Yellow | 8 | 48 | 0.5 | 1 | 3000 | 3 |
| SupraPlus-X 3000 1.5m | Yellow | 8 | 48 | 0.5 | 1.5 | 3000 | 3 |
| SupraPlus-X 3000 2.0m | Yellow | 8 | 48 | 0.5 | 2 | 3000 | 3 |
| SupraPlus-X 3000 2.5m | Yellow | 8 | 48 | 0.5 | 2.5 | 3000 | 3 |
| SupraPlus-X 3000 3.0m | Yellow | 8 | 48 | 0.5 | 3 | 3000 | 3 |
| SupraPlus-X 3000 3.5m | Yellow | 8 | 48 | 0.5 | 3.5 | 3000 | 3 |
| SupraPlus-X 3000 4.0m | Yellow | 8 | 48 | 0.5 | 4 | 3000 | 3 |
| SupraPlus-X 3000 5.0m | Yellow | 8 | 48 | 0.5 | 5 | 3000 | 3 |



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

| Item Name short | Colour | Contact Thickness Under Load [mm] | Contact Width Under Load [mm] | Dimension L1 min [m] | Dimension L1 [m] | WLL kg [kg] | WLL t [t] |
|-----------------------|--------|-----------------------------------|-------------------------------|----------------------|------------------|-------------|-----------|
| SupraPlus-X 3000 6.0m | Yellow | 8 | 48 | 0.5 | 6 | 3000 | 3 |
| SupraPlus-X 3000 7.0m | Yellow | 8 | 48 | 0.5 | 7 | 3000 | 3 |
| SupraPlus-X 3000 8.0m | Yellow | 8 | 48 | 0.5 | 8 | 3000 | 3 |
| SupraPlus-X 4000 0.5m | Grey | 9 | 54 | 0.75 | 0.5 | 4000 | 4 |
| SupraPlus-X 4000 1.0m | Grey | 9 | 54 | 0.75 | 1 | 4000 | 4 |
| SupraPlus-X 4000 1.5m | Grey | 9 | 54 | 0.75 | 1.5 | 4000 | 4 |
| SupraPlus-X 4000 2.0m | Grey | 9 | 54 | 0.75 | 2 | 4000 | 4 |
| SupraPlus-X 4000 2.5m | Grey | 9 | 54 | 0.75 | 2.5 | 4000 | 4 |
| SupraPlus-X 4000 3.0m | Grey | 9 | 54 | 0.75 | 3 | 4000 | 4 |
| SupraPlus-X 4000 4.0m | Grey | 9 | 54 | 0.75 | 4 | 4000 | 4 |
| SupraPlus-X 4000 5.0m | Grey | 9 | 54 | 0.75 | 5 | 4000 | 4 |
| SupraPlus-X 4000 6.0m | Grey | 9 | 54 | 0.75 | 6 | 4000 | 4 |
| SupraPlus-X 4000 7.0m | Grey | 9 | 54 | 0.75 | 7 | 4000 | 4 |
| SupraPlus-X 4000 8.0m | Grey | 9 | 54 | 0.75 | 8 | 4000 | 4 |
| SupraPlus-X 5000 0.5m | Red | 11 | 59 | 0.75 | 0.5 | 5000 | 5 |
| SupraPlus-X 5000 1.0m | Red | 11 | 59 | 0.75 | 1 | 5000 | 5 |
| SupraPlus-X 5000 1.5m | Red | 11 | 59 | 0.75 | 1.5 | 5000 | 5 |
| SupraPlus-X 5000 2.0m | Red | 11 | 59 | 0.75 | 2 | 5000 | 5 |
| SupraPlus-X 5000 2.5m | Red | 11 | 59 | 0.75 | 2.5 | 5000 | 5 |
| SupraPlus-X 5000 3.0m | Red | 11 | 59 | 0.75 | 3 | 5000 | 5 |
| SupraPlus-X 5000 3.5m | Red | 11 | 59 | 0.75 | 3.5 | 5000 | 5 |



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

| Item Name short | Colour | Contact Thickness Under Load [mm] | Contact Width Under Load [mm] | Dimension L1 min [m] | Dimension L1 [m] | WLL kg [kg] | WLL t [t] |
|-----------------------|--------|-----------------------------------|-------------------------------|----------------------|------------------|-------------|-----------|
| SupraPlus-X 5000 4.0m | Red | 11 | 59 | 0.75 | 4 | 5000 | 5 |
| SupraPlus-X 5000 5.0m | Red | 11 | 59 | 0.75 | 5 | 5000 | 5 |
| SupraPlus-X 5000 6.0m | Red | 11 | 59 | 0.75 | 6 | 5000 | 5 |
| SupraPlus-X 5000 7.0m | Red | 11 | 59 | 0.75 | 7 | 5000 | 5 |
| SupraPlus-X 6000 1.0m | Brown | 11 | 68 | 0.75 | 1 | 6000 | 6 |
| SupraPlus-X 6000 1.5m | Brown | 11 | 68 | 0.75 | 1.5 | 6000 | 6 |
| SupraPlus-X 6000 2.0m | Brown | 11 | 68 | 0.75 | 2 | 6000 | 6 |
| SupraPlus-X 6000 2.5m | Brown | 11 | 68 | 0.75 | 2.5 | 6000 | 6 |
| SupraPlus-X 6000 3.0m | Brown | 11 | 68 | 0.75 | 3 | 6000 | 6 |
| SupraPlus-X 6000 4.0m | Brown | 11 | 68 | 0.75 | 4 | 6000 | 6 |
| SupraPlus-X 6000 5.0m | Brown | 11 | 68 | 0.75 | 5 | 6000 | 6 |
| SupraPlus-X 6000 6.0m | Brown | 11 | 68 | 0.75 | 6 | 6000 | 6 |
| SupraPlus-X 6000 7.0m | Brown | 11 | 68 | 0.75 | 7 | 6000 | 6 |
| SupraPlus-X 6000 8.0m | Brown | 11 | 68 | 0.75 | 8 | 6000 | 6 |
| SupraPlus-X 8000 1.0m | Blue | 13 | 74 | 0.75 | 1 | 8000 | 8 |
| SupraPlus-X 8000 1.5m | Blue | 13 | 74 | 0.75 | 1.5 | 8000 | 8 |
| SupraPlus-X 8000 2.0m | Blue | 13 | 74 | 0.75 | 2 | 8000 | 8 |
| SupraPlus-X 8000 2.5m | Blue | 13 | 74 | 0.75 | 2.5 | 8000 | 8 |
| SupraPlus-X 8000 3.0m | Blue | 13 | 74 | 0.75 | 3 | 8000 | 8 |
| SupraPlus-X 8000 4.0m | Blue | 13 | 74 | 0.75 | 4 | 8000 | 8 |
| SupraPlus-X 8000 5.0m | Blue | 13 | 74 | 0.75 | 5 | 8000 | 8 |



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

| Item Name short | Colour | Contact Thickness Under Load [mm] | Contact Width Under Load [mm] | Dimension L1 min [m] | Dimension L1 [m] | WLL kg [kg] | WLL t [t] |
|-----------------------|--------|-----------------------------------|-------------------------------|----------------------|------------------|-------------|-----------|
| SupraPlus-X 8000 6.0m | Blue | 13 | 74 | 0.75 | 6 | 8000 | 8 |
| SupraPlus-X 8000 7.0m | Blue | 13 | 74 | 0.75 | 7 | 8000 | 8 |
| SupraPlus-X 8000 8.0m | Blue | 13 | 74 | 0.75 | 8 | 8000 | 8 |

| Item Name short | Weight Net [kg] | Weight per Meter [kg/m] |
|------------------------|-----------------|-------------------------|
| SupraPlus-X 500 0.5m | 0.1 | 0.2 |
| SupraPlus-X 500 0.75m | 0.15 | 0.2 |
| SupraPlus-X 500 1.0m | 0.2 | 0.2 |
| SupraPlus-X 500 1.5m | 0.3 | 0.2 |
| SupraPlus-X 500 2.0m | 0.4 | 0.2 |
| SupraPlus-X 500 2.5m | 0.4 | 0.2 |
| SupraPlus-X 500 3.0m | 0.4 | 0.2 |
| SupraPlus-X 500 5.0m | 0.4 | 0.2 |
| SupraPlus-X 1000 0.5m | 0.15 | 0.3 |
| SupraPlus-X 1000 0.75m | 0.22 | 0.3 |
| SupraPlus-X 1000 1.0m | 0.3 | 0.3 |
| SupraPlus-X 1000 1.5m | 0.45 | 0.3 |
| SupraPlus-X 1000 2.0m | 0.6 | 0.3 |
| SupraPlus-X 1000 2.5m | 0.75 | 0.3 |
| SupraPlus-X 1000 3.0m | 0.9 | 0.3 |
| SupraPlus-X 1000 4.0m | 1.2 | 0.3 |
| SupraPlus-X 1000 5.0m | 1.5 | 0.3 |
| SupraPlus-X 1000 6.0m | 2.4 | 0.3 |
| SupraPlus-X 1000 10m | 4 | 0.3 |
| SupraPlus-X 2000 0.5m | 0.25 | 0.5 |
| SupraPlus-X 2000 0.75m | 0.37 | 0.5 |
| SupraPlus-X 2000 1.0m | 0.5 | 0.5 |
| SupraPlus-X 2000 1.5m | 0.75 | 0.5 |
| SupraPlus-X 2000 2.0m | 1 | 0.5 |
| SupraPlus-X 2000 2.5m | 1.25 | 0.5 |



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

| Item Name short | Weight Net [kg] | Weight per Meter [kg/m] |
|-----------------------|-----------------|-------------------------|
| SupraPlus-X 2000 3.0m | 1.5 | 0.5 |
| SupraPlus-X 2000 4.0m | 2 | 0.5 |
| SupraPlus-X 2000 5.0m | 2.5 | 0.5 |
| SupraPlus-X 2000 6.0m | 3 | 0.5 |
| SupraPlus-X 2000 7.0m | - | 0.5 |
| SupraPlus-X 2000 8.0m | - | 0.5 |
| SupraPlus-X 3000 0.5m | - | 0.6 |
| SupraPlus-X 3000 1.0m | 0.6 | 0.6 |
| SupraPlus-X 3000 1.5m | 0.9 | 0.6 |
| SupraPlus-X 3000 2.0m | 1.2 | 0.6 |
| SupraPlus-X 3000 2.5m | 1.5 | 0.6 |
| SupraPlus-X 3000 3.0m | 1.8 | 0.6 |
| SupraPlus-X 3000 3.5m | 2 | 0.6 |
| SupraPlus-X 3000 4.0m | 2.4 | 0.6 |
| SupraPlus-X 3000 5.0m | 3.0 | 0.6 |
| SupraPlus-X 3000 6.0m | 3.6 | 0.6 |
| SupraPlus-X 3000 7.0m | - | 0.6 |
| SupraPlus-X 3000 8.0m | - | 0.6 |
| SupraPlus-X 4000 0.5m | 0.4 | 0.8 |
| SupraPlus-X 4000 1.0m | 0.8 | 0.8 |
| SupraPlus-X 4000 1.5m | 1.2 | 0.8 |
| SupraPlus-X 4000 2.0m | 1.6 | 0.8 |
| SupraPlus-X 4000 2.5m | 2 | 0.8 |
| SupraPlus-X 4000 3.0m | 2.4 | 0.8 |
| SupraPlus-X 4000 4.0m | 3.2 | 0.8 |
| SupraPlus-X 4000 5.0m | 4 | 0.8 |
| SupraPlus-X 4000 6.0m | 4.8 | 0.8 |
| SupraPlus-X 4000 7.0m | - | 0.8 |
| SupraPlus-X 4000 8.0m | - | 0.8 |
| SupraPlus-X 5000 0.5m | 2 | 1.0 |
| SupraPlus-X 5000 1.0m | 1 | 1.0 |
| SupraPlus-X 5000 1.5m | 1.5 | 1.0 |
| SupraPlus-X 5000 2.0m | 2 | 1.0 |



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

| Item Name short | Weight Net [kg] | Weight per Meter [kg/m] |
|-----------------------|-----------------|-------------------------|
| SupraPlus-X 5000 2.5m | 2.5 | 1.0 |
| SupraPlus-X 5000 3.0m | 3 | 1.0 |
| SupraPlus-X 5000 3.5m | 3.5 | 1.0 |
| SupraPlus-X 5000 4.0m | 4 | 1.0 |
| SupraPlus-X 5000 5.0m | 5 | 1.0 |
| SupraPlus-X 5000 6.0m | 6 | 1.0 |
| SupraPlus-X 5000 7.0m | - | 1.0 |
| SupraPlus-X 6000 1.0m | 1.2 | 1.2 |
| SupraPlus-X 6000 1.5m | 1.8 | 1.2 |
| SupraPlus-X 6000 2.0m | 2.4 | 1.2 |
| SupraPlus-X 6000 2.5m | 3 | 1.2 |
| SupraPlus-X 6000 3.0m | 3.6 | 1.2 |
| SupraPlus-X 6000 4.0m | 4.8 | 1.2 |
| SupraPlus-X 6000 5.0m | 6 | 1.2 |
| SupraPlus-X 6000 6.0m | 7.2 | 1.2 |
| SupraPlus-X 6000 7.0m | 8.4 | 1.2 |
| SupraPlus-X 6000 8.0m | 9.6 | 1.2 |
| SupraPlus-X 8000 1.0m | 1.6 | 1.6 |
| SupraPlus-X 8000 1.5m | 2.4 | 1.6 |
| SupraPlus-X 8000 2.0m | - | 1.6 |
| SupraPlus-X 8000 2.5m | 4 | 1.6 |
| SupraPlus-X 8000 3.0m | 4.8 | 1.6 |
| SupraPlus-X 8000 4.0m | 6.4 | 1.6 |
| SupraPlus-X 8000 5.0m | 8 | 1.6 |
| SupraPlus-X 8000 6.0m | 9.6 | 1.6 |
| SupraPlus-X 8000 7.0m | 10.6 | 1.6 |
| SupraPlus-X 8000 8.0m | 12 | 1.6 |



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

ORDER NUMBERS

| Dimension L1 | 500 kg | 1000 kg | 2000 kg | 3000 kg | 4000 kg | 5000 kg | 6000 kg | 8000 kg |
|--------------|---------|---------|---------|---------|---------|---------|---------|---------|
| 0.5 | 2019184 | 2019189 | 2019198 | 2027101 | 2027104 | 2027105 | - | - |
| 0.75 | 2019185 | 2019190 | 2019199 | - | - | - | - | - |
| 1 | 2019186 | 2019191 | 2019200 | 2019208 | 2024570 | 2024811 | 2024571 | 2024816 |
| 1.5 | 2019187 | 2019192 | 2019201 | 2019209 | 2024669 | 2024812 | 2024814 | 2024817 |
| 2 | 2019188 | 2019193 | 2019202 | 2019210 | 2019216 | 2019222 | 2022135 | 2022140 |
| 2.5 | 2027097 | 2019194 | 2019203 | 2019211 | 2019217 | 2024813 | 2024815 | 2024818 |
| 3 | 2027098 | 2019195 | 2019204 | 2019212 | 2019218 | 2019223 | 2022136 | 2022141 |
| 3.5 | - | - | - | 2027103 | - | 2027106 | - | - |
| 4 | - | 2019196 | 2019205 | 2019213 | 2019219 | 2019224 | 2022137 | 2022142 |
| 5 | 2027099 | 2019197 | 2019206 | 2019214 | 2019220 | 2019225 | 2022138 | 2022143 |
| 6 | - | 2024660 | 2019207 | 2019215 | 2019221 | 2019226 | 2022139 | 2022144 |
| 7 | - | - | 2024663 | 2024665 | 2024667 | 2024670 | 2024672 | 2024819 |
| 8 | - | - | 2024664 | 2024666 | 2024668 | - | 2024673 | 2024820 |
| 10 | - | 2027100 | - | - | - | - | - | - |

| | |
|-------------------------------|------------------|
| ■ Main Material | Polyester |
| ■ Temperature Range | - 40 bis + 100°C |
| ■ Safety Factor | 7:1 |
| ■ Label Protection | Yes |
| ■ Packaging Unit (PU) | pcs |
| ■ Packaging Unit (PU) Content | 1 |

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom